Technical Data

HN Sunlight

MagicSun

OH M 400 S, 45006328

Hg metal halide lamp

Dimensions:

la: 106,0 mm $^{+0,0}_{-3,0}$	lc: 31,0 mm	le:
lb: 93,0 mm	ld:	da:13,5 mm
Connection / socket:	R7s	



Electrical data:

Lamp wattage:	380 W
Lamp voltage:	135 (±15,0)V
Lamp current:	3,2 A
Line voltage:	230 V
Ballast:	N 400-03.2-34/12 Fa. M+C
Ignitor:	ZRM 4.5 ES/B

Operating conditions:

Burning position:	horizontal
Body temperature:	650℃ - 950℃
Pinch temperature:	< 300℃
Ignition retardation:	30 s

Life time:

Useful lifetime:	1000 h
Intensity drop:	<= 20 % 315-400 nm nm after 700 h - based on 20 h level
Power switching:	25' / 5' (on/off) On/Off

All data is based on average values. Due to technical and/or physical reason each lamp could spread up to +/- 10 %..





HN Sunlight GmbH
Original Hanau SunCare
Wilhelm-Rohn-Straße 25
D-63450 Hanau
Phone: 06181 / 35-5092
Fax.: 06181 / 35-5096
E-Mail: info@original-hanau-suncera.com
www.original-hanau-suncare.com

CE

ORIGINAL HANAU SUNCARE

31. Mrz. 08