# Technical Data

NewColors

# OH N 400 S, 45002245

Hg metal halide lamp

***Dimensions:***

la: 106,0 mm $^{+0,0}_{-3,0}$ lc: 31,0 mm le:

lb: 93,0 mm ld: da:13,5 mm

Connection / socket: R7s




**Electrical data:**

| | |
|---|---|
| Lamp wattage: | 380 W |
| Lamp voltage: | 135 (±15,0)V |
| Lamp current: | 3,2 A |
| Line voltage: | 230 V |
| Ballast: | N 400-03.2-34/12 Fa. M+C |
| Ignitor: | ZRM 4.5 ES/B |

**Operating conditions:**

| | |
|---|---|
| Burning position: | horizontal |
| Body temperature: | 650℃ - 950℃ |
| Pinch temperature: | < 300℃ |
| Ignition retardation: | 30 s |

***Life time:***

| | |
|---|---|
| Useful lifetime: | 750 h |
| Intensity drop: | <= 30 % 315-400 nm nm after 600 h - based on 20 h level |
| Power switching: | 25' / 5' (on/off) On/Off |

All data is based on average values. Due to technical and/or physical reason each lamp could spread up to +/- 10 %..







**Heraeus Noblelight GmbH**
Original Hanau SunCare
Heraeusstraße 12-14
D-63450 Hanau
Phone: 06181 / 35-5092
Fax.: 06181 / 35-5096
E-Mail: suncare@heraeus.com
www.heraeus-noblelight.com

CE

ORIGINAL HANAU SUNCARE

23. Apr. 07