

Technical Data

CLASSICS

OH C 2400 L, 45006414

Hg metal halide lamp

Dimensions:

la: 220,0 mm ^{+1,5} _{-1,5} lc: 104,0 mm le:
 lb: 168,0 mm ld: 400,0 mm ^{+5,0} _{-5,0} da: 24,5 mm

Connection / socket: Litzen / Aderendhülsen

Electrical data:


Lamp wattage: 2.400 W
 Lamp voltage: 250 (±15,0)V
 Lamp current: 11,0 A
 Line voltage: 400 V
 Ballast: ISO Italia by C&P 2400 W
 Ignitor: ZRM 12 ES/B 400

Operating conditions:



Burning position: vertical
 Body temperature: 650 °C - 950 °C
 Pinch temperature: < 300 °C
 Ignition retardation: 20 s

Life time:

Useful lifetime: 800 h
 Intensity drop: ≤ 30 % 315-400 nm nm after
 600 h - based on 20 h level
 Power switching: 25' / 5' (on/off) On/Off



All data is based on average values. Due to technical and/or physical reason each lamp could spread up to +/- 10 %..



Heraeus Noblelight GmbH
 Original Hanau SunCare
 Heraeusstraße 12-14
 D-63450 Hanau
 Phone: 06181 / 35-5092
 Fax.: 06181 / 35-5096
 E-Mail: suncare@heraeus.com
www.heraeus-noblelight.com

